



TI001en

Technical Information

thermokon
asia pacific

TPA0- Series (A)

Thermowell
used with Thermokon's Duct Sensors

The TPA0- Series (A) is designed to be used with Thermokon's Duct
Temperature Sensors

The Thermowells are used in hot or cold water pipe systems

The Thermowells designed for industrial applications

Several immersion lengths are available

Easy installation



Product Range

Order Code	Product	Immersion Lengths (mm)	Thread	max. flow	Pressure Rating	Material	max. Temp.	Applicable Products
TPA0.Ga	ø9x50	36	G1/2"	28m/s	PN40	V4A	260°C	TD1.AE ; TD12Axa ; TPI1.AE ; TPI2.Ax ; TUU1.xx ; TUU2.xx
TPA0.Ma	ø9x100	86		11m/s				TD1.GE ; TD12Gxa ; TPI1.GE ; TPI2.Gx ; TUU1.xx ; TUU2.xx
TPA0.Ha	ø9x150	136		7m/s				TD1.BE ; TD12Bxa ; TPI1.BE ; TPI2.Bx ; TUU1.xx ; TUU2.xx
TPA0.Ia	ø9x200	186		6m/s				TD1.CE ; TD12Cxa ; TPI1.CE ; TPI2.Cx ; TUU1.xx ; TUU2.xx
TPA0.Ka	ø9x250	236		3m/s				TD1.FE ; TD12Fxa ; TPI2.Fx ; TUU1.xx ; TUU2.xx
TPA0.La	ø9x300	286		2m/s				TD1.DE ; TD12Dxa ; TPI2.Dx ; TUU1.xx ; TUU2.xx
TPA0.Na	ø9x450	436		1m/s				TD1.EE ; TD12Exa ; TPI2.Ex ; TUU1.xx ; TUU2.xx

Dimensional Drawing

